

CLAIMS

What is Claimed is:

1. A method of executing a plurality of tasks of different priority values, said method comprising:

5 utilizing preemptive multitasking; and

utilizing cooperative multitasking, wherein said preemptive multitasking and said cooperative multitasking increase utilization of processing power of a processor and ensure higher priority valued tasks are executed with less interruption than lower priority valued tasks, and wherein each task is able to request a particular waiting

10 period during execution.

2. The method as recited in Claim 1 further comprising:

selecting a task from said tasks based on said priority values and a plurality of statuses associated with said tasks, wherein said statuses include executing, waiting,

15 interrupted, completed, and unstarted;

starting said selected task and designating said selected task an executing task;

if said executing task requests a waiting period, suspending said executing task and designating said executing task a waiting task and repeating said selecting said task and said starting said selected task;

20 if said waiting period elapses for any waiting task and said executing task has a higher priority value than said waiting task, designating said waiting task an interrupted task;

if said waiting period elapses for any waiting task and said executing task does not have a higher priority value than said waiting task, suspending said executing task and designating said executing task an interrupted task and repeating said selecting said task and said starting said selected task; and

5 if said executing task completes execution, designating said executing task a completed task and repeating said selecting said task and said starting said selected task.

3. The method as recited in Claim 2 wherein said selecting said task
10 includes:

selecting higher priority values before selecting lower priority values when possible.

4. The method as recited in Claim 2 wherein said selecting said task
15 includes:

if a first particular task cannot be executed until a second particular task has completed execution, enabling selection of said first particular task after said second particular task has completed execution.

20 5. The method as recited in Claim 2 further comprising:
setting a timer based on said waiting period.

6. The method as recited in Claim 1 wherein said tasks are BIOS (Basic Input Output System) initialization tasks.

7. The method as recited in Claim 6 wherein said waiting period is
5 requested from a BIOS kernel.

8. A computer-readable medium comprising computer-executable instructions stored therein for performing a method of executing a plurality of tasks of different priority values, said method comprising:

10 utilizing preemptive multitasking; and
utilizing cooperative multitasking, wherein said preemptive multitasking and said cooperative multitasking increase utilization of processing power of a processor and ensure higher priority valued tasks are executed with less interruption than lower priority valued tasks, and wherein each task is able to request a particular waiting
15 period during execution.

9. The computer-readable medium as recited in Claim 8 wherein said method further comprises:

selecting a task from said tasks based on said priority values and a plurality of
20 statuses associated with said tasks, wherein said statuses include executing, waiting, interrupted, completed, and unstarted;
starting said selected task and designating said selected task an executing task;

if said executing task requests a waiting period, suspending said executing task and designating said executing task a waiting task and repeating said selecting said task and said starting said selected task;

5 if said waiting period elapses for any waiting task and said executing task has a higher priority value than said waiting task, designating said waiting task an interrupted task;

if said waiting period elapses for any waiting task and said executing task does not have a higher priority value than said waiting task, suspending said executing task and designating said executing task an interrupted task and repeating said selecting
10 said task and said starting said selected task; and

if said executing task completes execution, designating said executing task a completed task and repeating said selecting said task and said starting said selected task.

15 10. The computer-readable medium as recited in Claim 9 wherein said selecting said task includes:

selecting higher priority values before selecting lower priority values when possible.

20 11. The computer-readable medium as recited in Claim 9 wherein said selecting said task includes:

if a first particular task cannot be executed until a second particular task has completed execution, enabling selection of said first particular task after said second particular task has completed execution.

5 12. The computer-readable medium as recited in Claim 9 further comprising:
 setting a timer based on said waiting period.

 13. The computer-readable medium as recited in Claim 8 wherein said tasks
are BIOS (Basic Input Output System) initialization tasks.

10

 14. The computer-readable medium as recited in Claim 13 wherein said
waiting period is requested from a BIOS kernel.

 15. A system comprising:

15

a processor; and

a BIOS (Basic Input Output System) operative to utilize preemptive multitasking
and cooperative multitasking to increase utilization of processing power of said
processor and to ensure higher priority valued initialization tasks are executed with
less interruption than lower priority valued initialization tasks when executing a
20 plurality of initialization tasks of different priority values, and wherein each initialization
task is able to request a particular waiting period during execution.

16. The system as recited in Claim 15 wherein when executing said initialization tasks, said BIOS selects an initialization task having a higher priority value before selecting an initialization task having a lower priority value when possible.

5

17. The system as recited in Claim 15 wherein if a first particular initialization task cannot be executed until a second particular initialization task has completed execution, said BIOS enables selection of said first particular initialization task after said second particular initialization task has completed execution.

10

18. The system as recited in Claim 15 further comprising:
a timer.

19. The system as recited in Claim 15 wherein said BIOS includes a BIOS
15 kernel for receiving requests for said particular waiting period from said initialization tasks.

20. The system as recited in Claim 15 further comprising a plurality of
hardware components.

20